

PT250 - PT275S



| Ratings @ 0.8 PF | | Prime Rating | Stand-by Rating |
|-----------------------------|-------------------------------|----------------------------|----------------------------|
| Voltage*¹ | Frequency*² | PT 250*³ | PT 275*⁴ |
| 230/400 V | 50 Hz | 250 KVA | 275 KVA |
| 277/480 V | 60 Hz | 290 KVA | 322.8 KVA |

The above ratings represent the generating set capability guaranteed within $\pm 3\%$ at the reference conditions equivalent to those specified in ISO 8528/1.



Notes

1. The applicable voltage range is 380V to 415V for 50Hz applications and 380V to 480V for 60Hz applications. For other voltage consult factory.

2. This generating set is of switchable speed of 1500rpm and 1800rpm.

3. PT250 is the prime power rating of the generating set, where a variable load and unlimited hours usage are applied on the generating set with an average load factor of 80% of the prime rating over each 24 hour period. Noting that a 10% overload is available for 1 hour in every 12 hours operation.

4. PT275S is the standby power rating of the generating set, where a variable load limited to an annual usage up to 500 hours is applied, with 300 hours of which may be continuous running. Noting that no overload is permitted.

Certifications



- The complete Generating Set is type-tested according to ISO 8528-8 Standard.



ISO 17025
ACCREDITED
LABORATORY

- The control panel is certified by an ISO 17025 accredited laboratory to have IP55 according to IEC 60355



Quality
ISO 9001
SAI GLOBAL

Dimensions

| | |
|---------------|---------|
| Length | 3000 mm |
| Width | 990 mm |
| Height | 1710 mm |
| Weight | 2417 Kg |

Technical Data

Engine model

Perkins 1506A-E88TAG3

Cylinders

6 - vertical in-line

Aspiration

Turbocharged & Aftercooled

Combustion

Direct injection

Cooling System

Water cooled

Displacement

8.8 liters

Oil consumption

0.1 % of fuel consumption

Lube oil capacity

41 liters

Coolant capacity

29.6 liters

Governor

Electronic

Speed

1500 rpm

1800 rpm

Fuel Consumption @ 100% Load

56 L/H

63 L/H

Fuel Consumption @ 75% Load

42 L/H

48 L/H

Fuel Consumption @ 50% Load

29 L/H

33 L/H

Radiator Cooling Air Flow

370 m³/min

482 m³/min

Max exhaust gas flow

40.4 m³/min

48.9 m³/min

Emissions regulations

For unregulated territories

The above performance data are valid as per the following specs:

- Diesel Fuel is according to BS2869 Class A2 or equivalent.
- Lubricating oil is according to API CH4 (15W/40).
- The coolant should be 50% antifreeze and 50% distilled water.

Alternator model

Leroy Somer LSA 46.3 S5

Regulation

$\pm 0.5\%$

International protection

IP23

Insulation class

H

Terminals

12

Frequency

50 Hz

60 Hz

Coolant Air flow

0.48 m³/s

0.58 m³/s